

TINENZA

PORCELUX

CARACTERÍSTICAS TÉCNICAS

GRUPO B1a (GL) Absorción de agua < 0,5%
GROUP B1a (GL) Water absorption < 0,5%
GROUPE B1a (GL) Absorption d'eau < 0,5%

NORMAS DE ENSAYO
STANDARD
NORMES D'ESSAI

VALORES PRESCRITOS NORMA EN 14411
VALUE REQUIRED BY EN 14411 STANDARD
VALEURS PRESCRITES NORME EN 14411

VALOR MEDIO
AVERAGE VALUE
VALEUR MOYENNE



FORMATO	PRECIO	PZ/CJ	KG/CJ	M²/CJ	CJ/PL	KG/PL	M²/PL
90x180	PS-506	1	45,5	1,62	24	1.112	38,88
120x120	PS-460	1	38,4	1,44	36	1.402,40	51,84
90x90	PS-269	2	42	1,62	36	1.112	42,12
60x120	PS-290	2	33,2	1,44	30	996	43,2
75x75	PS-226	3	41,2	1,69	30	1.256	50,7

prissmacer
MADE WITH LOVE

AZULEJOS FOSET, S.L.U
CAMINO DEL PALMERAL, 10 APARTADO DE CORREOS 263
POL. IND. EL COLOMER 12200 ONDA (CASTELLÓN) ESPAÑA
TEL.: +34 964 500 226 | FAX.: +34 964 500 039
info@prissmacer.es | www.prissmacer.es

TINENZA

PORCELUX



prissmacer



TINENZA

PORCELUX



TINENZA

FORMATOS / FORMATS

